

HM

HRC


05220

Frese per stampi

Visit the online
Product Sheet

F05220H00250052

2 flute ball nose end mill for ribbing with tapered neck and reinforced shank

Silmax
NORM $\lambda 30^\circ$ 

Details

Diameter of cutting edge D +0/-0,02	2,50
Corner Radius/Radius Cr/r	1,25
Cutting length l	2,10
Neck Relief Length l1	10,0
Neck diameter d1	2,40
Neck Angle α	1,9
Engaged Angle β	12,0
Overall Length L	60
Shank Diameter d h6	6,00
$\varepsilon 0,5^\circ$ $\varepsilon 0,5^\circ$	4,44
$\varepsilon 1,0^\circ$ $\varepsilon 1,0^\circ$	6,22
$\varepsilon 2,0^\circ$ $\varepsilon 2,0^\circ$	10,52
$\varepsilon 3,0^\circ$ $\varepsilon 3,0^\circ$	11,53
Number of Flutes Z	2

Materials

Hardened steel 42 ÷ 52 HRC

Hardened steel 52 to 62 HRC

Coatings

Balinit® Tisaflex (HMH)

Alternative Coatings

Shank references standard
Rif. gambo HA

This tool is available in 9 diameters.

 Please consider the environment, before printing this document.