




Visit the online Product Sheet

HM0320010

VPlus endmill 60°



Details

Diameter of cutting edge D h9	1,00
Shank Diameter d h6	3,00
Overall Length L	39
Cutting length l	2,00
Front Angle α	60
Number of Flutes Z	2

Materials

Steel < 800 n/mm ²	<div style="width: 100%; height: 10px; background-color: #0070C0;"></div>
Steel < 1000 n/mm ²	<div style="width: 100%; height: 10px; background-color: #0070C0;"></div>
Steel < 1300 n/mm ²	<div style="width: 100%; height: 10px; background-color: #0070C0;"></div>
Ferritic/Martensitic steel	<div style="width: 100%; height: 10px; background-color: #FFC000;"></div>
Austenitic steel	<div style="width: 100%; height: 10px; background-color: #FFC000;"></div>
PH Duplex	<div style="width: 100%; height: 10px; background-color: #FFC000;"></div>
Grey cast iron	<div style="width: 100%; height: 10px; background-color: #D9534F;"></div>
Aluminium	<div style="width: 100%; height: 10px; background-color: #4CAF50;"></div>
Copper	<div style="width: 100%; height: 10px; background-color: #4CAF50;"></div>
Thermoplastic resin	<div style="width: 100%; height: 10px; background-color: #4CAF50;"></div>
Difficult-to-machine Superalloys	<div style="width: 100%; height: 10px; background-color: #795548;"></div>
Very difficult-to-machine Superalloys	<div style="width: 100%; height: 10px; background-color: #795548;"></div>


Coatings

- Uncoated (HM0)

- Alternative Coatings

- Balinit® Alcrona (HMG)

This tool is available in 8 diameters and 2 coatings.

 Please consider the environment, before printing this document.